

ADMINISTRATOR OF PROGRAMME OPERATOR



COL·LEGI D'APARELLADORS, ARQUITECTES TÈCNICS I ENGINYERS D'EDIFICACIÓ DE BARCELONA





DECLARACIÓN AMBIENTAL DE PRODUCTO ENVIRONMENTAL PRODUCT DECLARATION

DAPcons®. According to ISO 14025 and EN UNE 15804 + A2:2020





COL·LEGI D'APARELLADORS, ARQUITECTES TÈCNICS I ENGINYERS D'EDIFICACIÓ DE BARCELONA

Product

Owner

Product description

PCR Reference

Production plant

Validity

From:

To:

The validity of DAPcons® is subject to the conditions of DAPcons® regulations. The relevant version of this DAPcons® is included in the register kept by the CAATEEB; for more information, consult the Program Operator website: www.csostenible.net



ENVIRONMENTAL PRODUCT DECLARATION. EXECUTIVE SUMMARY

\frown		
dap ^{cons}		FOR DAPconstrucción® arations of construction sector
🔗 СААТЕЕВ	Administrator of Program Col·legi d'Aparelladors, Arqu Bon Pastor, 5 · 08021 Barce www.apabcn.cat	itectes Tècnics i Enginyers de l'Edificació de Barcelona
	Owner of the Declaration	
	Declaration carried out by	<i>r</i> :
Declared Product		
Product description		
Geographical repres	entativeness	
Maniah Ilitu katuraan	different products	
variability between o		

This verified declaration authorises the owner to use the DAPcons® eco-label logo. The declaration is applicable exclusively to the product in question and for five years as of the date of registration. The responsible for the information contained in this declaration is:

Endorsed by CAATEEB

Endorsed by authorised verifier





ENVIRONMENTAL PRODUCT DECLARATION 1. PRODUCT DESCRIPTION AND APPLICATION

This document comprises 18 pages. Its partial reproduction is prohibited











2. LIFE CYCLE PHASES DESCRIPTION

2.1. Manufacture (A1, A2 and A3)

Raw materials (A1 and A2)

Manufacturing (A3)

This document comprises 18 pages. Its partial reproduction is prohibited





2.2. Construction (A4 and A5)

Product transport to the building site (A4)

Table 1. Transport scenarios of product to the building site

Destination	Type of transport	Percentage (%)	Average Km
Spain			
Europe			
Rest of the world			
	·	Total 100%	

Construction and instalation process (A5)

This document comprises 18 pages. Its partial reproduction is prohibited





2.3. Product use (B1-B7)

2.4. End-of-life (C1-C4)

2.5. Benefits and loads beyond the system boundary (D)







3. LIFE CYCLE ASSESSEMENT

3.1. Unit

3.2. System boundary

Table 2. Declared modules

Product stage		Constr Proces Stage			Use stage			E	nd of li	fe stag	e	Benefits and loads beyond the system boundaries				
Raw materials supply	Transport	Manufacturing	Transport	Installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational Energy use	Operational water use	De-construction	Transport	Waste processing	Disposal	Reuse, recovery, recycling potential
A1	A2	A3	A4	A5	B1	B2	В3	B4	B5	B6	В7	C1	C2	C3	C4	D

X = Included in LCA MND = Module not Declared





3.3. Data analysis for the life cycle (LCA)

Table 3. Indicators of the environmental impact

A1 Raw materials suply. A2 Transport. A3 Manufacturing Product. A4 Transport A5 Construction – Installation process B1 Use. B2 Maintenance. B3 Repair. B4 Replacement. B5 Refurbisshment. B6 Operational Energy use. B7 Operational water use. C1 Decosntruction and demolition. C2 Transport. C3 Waste management for reuse, recovery and recycling. C4 Disposal. MND Module not declared. MJ Net calorific value.







Table 4. Use of resources, waste and material outflows parameters

EXCEL

A1 Raw materials suply. A2 Transport. A3 Manufacturing Product. A4 Transport A5 Construction – Installation process B1 Use. B2 Maintenance. B3 Repair. B4 Replacement. B5 Refurbisshment. B6 Operational Energy use. B7 Operational water use. C1 Decosntruction and demolition. C2 Transport. C3 Waste management for reuse, recovery and recycling. C4 Disposal. MND Module not declared. MJ Net calorific value.







Table 5. Kg of biogenic carbon

Product	Kg
Packaging	Kg

3.4. Recommendations of this DAP

3.5. Cut-off rules

3.6. Additional environmental information

3.7. Other data





4. TECHNICAL INFORMATION AND SCENARIOS

4.1. Transport from the factory to the building site (A4)

Parameter	Parameter expressed by functional unit
Type and fuel consumption, type of vehicle used for transportation	
Distance	
Capacity utilization (including empty return)	
Apparent density of transported product	
Useful capacity factor (1, <1, or> 1 for products that are packed compressed or nested)	

4.2. Installation processes (A5)

Parameter	Parameter expressed by functional unit
Construction ancillary materials (specifying each material)	
Water consumption	
Consumption of other resources	
Quantitive despription of the type of energy (mix regional) and consumption during the installation process	
Materials waste on site before waste treatment, generated by the installation of the product (specify by type)	
Material outputs (specified by type) as a result of waste treatment on the building site. For example: collection for recycling, energy valuation, disposal (specified by route)	
Emisions to the air, ground or water	





Reference service life (B1)

Parameter	Parameter expressed by functional unit
Reference service life (RSL)	
Properties and characteristics of the product	
Requirements (ways of using, maintenance frequency, repair, etc.)	

4.4. Maintenance (B2), repair (B3), replacement (B4) or refurbishement (B5)

B2 Maintenance				
Parameter	Parameter expressed by functional unit			
Maintenance, for example: cleaning agent, type of surfactant				
Maintenance cycle				
Auxiliar materials for the maintenance process (specifying each material)				
Net consumption of fresh water				
Loss of material during maintenance or repair (specifying the type)				







B3 Repair				
Parameter	Parameter expressed by functional unit			
Repair process				
Inspection process				
Repair cycle				
Auxiliary materials (specifying each material), e.g. lubricant				
Energy input during repair, vector type energy (for example, electricity) and quantity				
Energy input during the process of renovation (amount and type of energy vector)				
Loss of material during repair (specifying each material)				
Net consumption of fresh water				

B4 Replacement				
Parameter	Parameter expressed by functional unit			
Energy input during replacement, for example for the use of cranes (quantity and energy vector)				
Worn out parts replacement in the life cycle of the product (specifying each material)				
Replacement cycle				





B5 Rehabilitation					
Parameter	Parameter expressed by functional unit				
Rehabilitation process					
Rehabilitation cycle					
Energy input during rehabilitation, for example for the use of cranes (quantity and energy vector)					
Material input for rehabilitation, including auxiliary materials (specified by material)					
Material waste during rehabilitation (specifying each material)					
Other scenario development assumptions					

4.5. Useful life reference

Parameter	Parameter expressed by functional unit
Useful life reference	
Product declared properties, finishes, etc.	
Application design parameters (manufacturer's instructions)	
Workmanship quality estimation, when installed in accordance with the manufacturer's instructions	
Outdoor environment for outdoor applications. For example, weather, pollutants, UV radiation, temperature, etc.	





Indoor environment for indoor applications. For example, temperature, humidity, exposure to chemicals	
Terms of use. For example, frequency of use, mechanical exposure, etc.	
Maintenance. For example, the required frequency, etc.	

4.6. Operational use of energy (B6) and water (B7)

Parameter	Parameter expressed by functional unit
Construction ancillary materials (specified by material)	
Energy vector type. For example, electricity, natural gas, district heating	
Equipment output power	
Net fresh water consumption	
Characteristic features (energy efficiency, emissions, etc.)	
Other scenarios development assumptions. For example, transportation	





4.7. End of life (C1-C4)

Process	Parameter expressed by functional unit
Collection processes (specified by types)	
Recovery systems (specified by type)	
Elimination	
Assumptions for the development of scenarios. For example, transportation	

5. ADDITIONAL INFORMATION







6. PCR AND VERIFICATION

This declaration is based on the Document

Independent verification of the declaration and data according to ISO 14025 and UNE EN15804 + A2 $\,$

Internal Ex	ternal
-------------	--------

Independent verifier appointed

Verification date

References

Administrator of programme operator

Col·legi d'Aparelladors, Arquitectes Tècnics i Enginyers de l'Edificació de Barcelona (CAATEEB) Bon Pastor 5, 08021 Barcelona www.apabcn.cat

